





SPECIFICATIONS

Structure : RCC framed structure with brick filler walls (Earthquake resistant)

Toilets : Provisions of hot & cold water pipes in all toilet. Coloured glazed tile dado

upto 7 ft. Sanitary / Chinaware in light coloured shade of standard make

C.P. fittings of standard make.

Kitchen : Polished granite work top stainless steel sink with drain board. Glazed tile

dado on walls upto 2 ft. over counter.

Doors & Windows : All frames in wood duly painted. 35 mm thick commercial flush doors, duly

painted. Window shuttered in wood duly painted. Main entrance to be of

flush door suitably decorated on both sides.

Hardware : Shutter hinges in steel. All other fittings shall be anodized aluminium. All

doors except those in toilets & kitchen to be provided with a mortice lock.

Flooring : Vitrified tiles flooring in drawing/ dinning and all bedrooms. Ceramic tile

flooring in toilets and kitchen. Decorative patterned floor in passages &

lobbies

Internal Finishes : POP cornices in drawing/ dinning and in all bedrooms. Oil bound distemper

in pleasing shades on walls.

External Work : Electrical work with copper wires in concealed PVC conduits. Provision

shall be made for sufficient lighting, power points, TV aerial point in master

bedroom & living room. Telephone points in all rooms.

Gas supply : Provision for piped gas supply

Connectivity: Broad band connectivity.







